



HYGROW SDN. BHD.

18, Jalan KP 1/3, Kajang Prima,  
43000 Kajang, Selangor Darul Ehsan.  
Website: www.hygrow.com.my

Tel : +603 8739 4663  
Fax : +603 8739 4662  
Email : info@hygrow.com.my



VSL LED Product

Model	Specification
<p><b>VSL-HB</b></p>  <p><b>LED High Bay</b></p>	<p><b>Power</b> 70W / 100W / 150W  <b>Lumen</b> 7500lm / 10700lm / 15600lm  <b>LED</b> CREE XLamp XP-G2  <b>Beam Angle</b> 30°, 50°, 70°, 140°  <b>Dimension</b> Ø 350*283mm  <b>IP</b> -  <b>CCT</b> 5700K  <b>Rated Life</b> 50,000 hours  <b>Warranty</b> 3 years</p>
<p><b>VSL-TF7A</b></p>  <p><b>LED High Bay / Low Bay</b></p>	<p><b>Power</b> 100W / 150W / 200W  <b>Lumen</b> 10500lm / 15750lm / 21000lm  <b>LED</b> LUMILEDS 3030  <b>Beam Angle</b> 25°, 40°, 60°, 90°, 120°  <b>Dimension</b> Ø 472*225mm  <b>IP</b> IP68  <b>CCT</b> 3000K, 4000K, 5000K, 5700K  <b>Rated Life</b> 50,000 hours  <b>Warranty</b> 5 years</p>
<p><b>VSL-FL2C</b></p>  <p><b>LED Flood Light</b></p>	<p><b>Power</b> 50W / 100W / 150W / 200W  <b>Lumen</b> 5250lm / 10500lm / 15750lm / 21000lm  <b>LED</b> LUMILEDS 3030  <b>Beam Angle</b> 25°, 40°, 60°, 90°  <b>Dimension</b> 360*200*95 / 360*200*175 / 360*260*255 / 360*260*335mm  <b>IP</b> IP68  <b>CCT</b> 3000K, 4000K, 5000K, 5700K  <b>Rated Life</b> 50,000 hours  <b>Warranty</b> 3 years</p>
<p><b>VSL-T1B</b></p>  <p><b>LED Street Light</b></p>	<p><b>Power</b> 50W / 100W  <b>Lumen</b> 5250lm / 10500lm  <b>LED</b> LUMILEDS 3030  <b>Beam Angle</b> Type I, II, III, IV, VS  <b>Dimension</b> 500*295*88mm  <b>IP</b> IP68  <b>CCT</b> 3000K, 4000K, 5000K, 5700K  <b>Rated Life</b> 50,000 hours  <b>Warranty</b> 3 years</p>
<p><b>VSL-T11A</b></p>  <p><b>LED Street Light</b></p>	<p><b>Power</b> 150W / 200W  <b>Lumen</b> 15750lm / 21000lm  <b>LED</b> LUMILEDS 3030  <b>Beam Angle</b> Type I, II, III, IV, VS  <b>Dimension</b> 725*330*91mm / 805*330*91mm  <b>IP</b> IP68  <b>CCT</b> 3000K, 4000K, 5000K, 5700K  <b>Rated Life</b> 50,000 hours  <b>Warranty</b> 3 years</p>

Remarks: Input voltage: 100 ~ 240Vac 50/60Hz





**HYGROW SDN. BHD.**

18, Jalan KP 1/3, Kajang Prima,  
43000 Kajang, Selangor Darul Ehsan.  
Website: [www.hygrow.com.my](http://www.hygrow.com.my)

Tel : +603 8739 4663  
Fax : +603 8739 4662  
Email : [info@hygrow.com.my](mailto:info@hygrow.com.my)



**VSL LED Product**

Model	Specification
<p><b>VSL-SLBC</b></p>  <p><b>LED Slim T8 Bare Channel</b></p>	<p><b>Power</b> 1x9W / 1x18W / 2x9W / 2x18W  <b>Lumen</b> 900lm / 1800lm / 1800lm / 3600lm  <b>LED</b> SMD 2835  <b>Beam Angle</b> 160° / 330°  <b>Dimension</b> 1222*42*65mm  <b>IP</b> -  <b>CCT</b> 3000K, 4000K, 6000K  <b>Rated Life</b> 25,000 hours / 40,000 hours  <b>Warranty</b> 1 year / 2 years</p>
<p><b>VSL-SLBC</b></p>  <p><b>LED Slim T8 Bare Channel</b></p>	<p><b>Power</b> 1x8W / 1x16W / 1x20W / 2x8W / 2x16W / 2x20W  <b>Lumen</b> 800lm / 1600lm / 2050lm / 1600lm / 3200lm / 4100lm  <b>LED</b> GE Industry Grade T8 LED Tube  <b>Beam Angle</b> 150°  <b>Dimension</b> 1222*42*65mm  <b>IP</b> -  <b>CCT</b> 3000K, 4000K, 6500K  <b>Rated Life</b> 40,000 hours  <b>Warranty</b> 3 years</p>
<p><b>VSL-YSL</b></p>  <p><b>LED Anti-Corrosive</b></p>	<p><b>Power</b> 1x18W / 2x18W / 1x20W * / 2x20W*  <b>Lumen</b> 1800lm / 3200lm / 2050lm / 4100lm  <b>LED</b> SMD 2835 / *GE Industry Grade T8 LED Tube  <b>Beam Angle</b> 160° / 330° / *150°  <b>Dimension</b> 1265*90*88mm / 1265*130*88mm  <b>IP</b> IP65  <b>CCT</b> 3000K, 4000K, 6500K  <b>Rated Life</b> 25,000 hours / 40,000 hours  <b>Warranty</b> 1 year, 2 years, *3 years</p>
<p><b>VSL-R</b></p>  <p><b>LED Recessed Light</b></p>	<p><b>Power</b> 2x9W / 2x18W  <b>Lumen</b> 1800lm / 3600lm  <b>LED</b> SMD 3825  <b>Beam Angle</b> 160° / 150°  <b>Dimension</b> 610*603*90mm / 1220*603*90mm  <b>IP</b> -  <b>CCT</b> 3000K, 4000K, 6500K  <b>Rated Life</b> 25,000 hours / 40,000 hours  <b>Warranty</b> 1 year, 2 years</p>
<p><b>VSL-P</b></p>  <p><b>LED Premium Light</b></p>	<p><b>Power</b> 2x20W / 4x20W  <b>Lumen</b> 4000lm / 8000lm  <b>LED</b> GE Industry Grade T8 LED Tube  <b>Beam Angle</b> 150°  <b>Dimension</b> 1233*292*180mm / 1233*506*180mm  <b>IP</b> IP40  <b>CCT</b> 3000K, 4000K, 6500K  <b>Rated Life</b> 40,000 hours  <b>Warranty</b> 3 years</p>

Remarks: Input voltage: 100 ~ 240Vac 50/60Hz





HYGROW SDN. BHD.

18, Jalan KP 1/3, Kajang Prima,  
43000 Kajang, Selangor Darul Ehsan.  
Website: www.hygrow.com.my

Tel : +603 8739 4663  
Fax : +603 8739 4662  
Email : info@hygrow.com.my



VSL LED Product

Model	Specification
<p><b>VSL-MDL</b></p>  <p><b>LED Modular Downlight</b></p>	<p><b>Power</b> 12W* / 15W / 19W / 24W  <b>Lumen</b> 900lm* / 1200lm / 1500lm / 2000lm  <b>LED</b> PHILIPS  <b>Beam Angle</b> 100°  <b>Dimension</b> 4" / 6" / 8"  <b>IP</b> IP20  <b>CCT</b> 3000K, 4000K, 5000K  <b>Rated Life</b> 25,000 hours  <b>Warranty</b> 2 years</p>
<p><b>VSL-PL22</b></p>  <p><b>LED Panel Light 2x2</b></p>	<p><b>Power</b> 40W  <b>Lumen</b> 3700lm  <b>LED</b> PHILIPS Certaflux  <b>Beam Angle</b> 100°  <b>Dimension</b> 50*603*603mm  <b>IP</b> IP40  <b>CCT</b> 4000K, 5000K, 6500K  <b>Rated Life</b> 50,000 hours  <b>Warranty</b> 3 years</p>
<p><b>VSL-LB-SQ</b></p>  <p><b>LED Low Bay Light (Square)</b></p>	<p><b>Power</b> 50W / 100W  <b>Lumen</b> 7200lm / 14400lm  <b>LED</b> PHILIPS Fortimo HF  <b>Beam Angle</b> 100°  <b>Dimension</b> 100*325*450mm / 100*450*450mm  <b>IP</b> IP20  <b>CCT</b> 4000K, 5000K, 6500K  <b>Rated Life</b> 50,000 hours  <b>Warranty</b> 5 years</p>
<p><b>LED-LB-RD</b></p>  <p><b>LED Low Bay Light (Round)</b></p>	<p><b>Power</b> 50W / 100W  <b>Lumen</b> 5400lm / 10800lm  <b>LED</b> OSRAM PREVA SKY  <b>Beam Angle</b> 90°  <b>Dimension</b> Ø 460*295mm  <b>IP</b> IP20  <b>CCT</b> 6500K  <b>Rated Life</b> 50,000 hours  <b>Warranty</b> 5 years</p>
<p><b>VSL-WB-LCF</b></p>  <p><b>LED Wide Batten</b></p>	<p><b>Power</b> 30W / 40W  <b>Lumen</b> 2720lm / 3740lm  <b>LED</b> PHILIPS Certaflux  <b>Beam Angle</b> 120°  <b>Dimension</b> 60*63*1168mm  <b>IP</b> IP40  <b>CCT</b> 4000K, 5000K, 6500K  <b>Rated Life</b> 50,000 hours  <b>Warranty</b> 3 years</p>

Remarks: Input voltage: 100 ~ 240Vac 50/60Hz





HYGROW SDN. BHD.

18, Jalan KP 1/3, Kajang Prima,  
43000 Kajang, Selangor Darul Ehsan.  
Website: www.hygrow.com.my

Tel : +603 8739 4663  
Fax : +603 8739 4662  
Email : info@hygrow.com.my



VSL LED Product

Model	Specification
<p><b>VSL-RL14</b></p>  <p><b>LED Recessed Light</b></p>	<p><b>Power</b> 40W  <b>Lumen</b> 3740lm  <b>LED</b> PHILIPS Certaflux  <b>Beam Angle</b> 100°  <b>Dimension</b> 50*303*1212mm  <b>IP</b> IP20  <b>CCT</b> 4000K, 5000K, 6500K  <b>Rated Life</b> 50,000 hours  <b>Warranty</b> 3 years</p>
<p><b>VSL-LAC</b></p>  <p><b>LED Anti-Corrosive LAC</b></p>	<p><b>Power</b> 30W / 40W  <b>Lumen</b> 2720lm / 3700lm  <b>LED</b> PHILIPS Certaflux / Fortimo / OSRAM  <b>Beam Angle</b> 120°  <b>Dimension</b> 100*102*1265mm  <b>IP</b> IP65  <b>CCT</b> 4000K, 5000K, 6500K  <b>Rated Life</b> 50,000 hours  <b>Warranty</b> 3 years</p>
<p><b>VSL-SS-HB</b></p>  <p><b>LED Stainless Steel High Bay</b></p>	<p><b>Power</b> 100W / 150W / 200W  <b>Lumen</b> 10500±500lm / 14850±750lm / 18900±1000lm  <b>LED</b> LUMILEDS LUXEON 3030 2D  <b>Beam Angle</b> 25°, 40°, 60°, 90°, 120°  <b>Dimension</b> 400*300mm*110mm  <b>IP</b> IP68  <b>CCT</b> 3000K, 4000K, 5000K, 5700K  <b>Rated Life</b> 50,000 hours  <b>Warranty</b> 3 years</p>
<p><b>VSL-UFO-III</b></p>  <p>Emergency / Dimming / Motion &amp; Daylight Sensor  <b>LED UFO High Bay III</b></p>	<p><b>Power</b> 100W / 150W / 200W  <b>Lumen</b> 12000-13000lm / 18000-19500lm / 24000-26000lm  <b>LED</b> LUMILEDS LUXEON 3030 2D  <b>Beam Angle</b> 60°, 90°, 120°  <b>Dimension</b> Ø 320*187mm / Ø 320*187mm / Ø 400*208mm  <b>IP</b> IP65  <b>CCT</b> 3000K, 4000K, 5000K, 5700K  <b>Rated Life</b> 50,000 hours  <b>Warranty</b> 5 years</p>
<p><b>VSL-UFO-IV</b></p>  <p>Emergency / Dimming / Motion &amp; Daylight Sensor  <b>LED UFO High Bay IV</b></p>	<p><b>Power</b> 100W / 150W / 200W  <b>Lumen</b> 13000-14000lm / 19500-21000lm / 26000-28000lm  <b>LED</b> LUMILEDS LUXEON 3030 2D  <b>Beam Angle</b> 120°  <b>Dimension</b> Ø 360*200mm / Ø 430*210mm / Ø 530*220mm  <b>IP</b> IP65  <b>CCT</b> 3000K, 4000K, 5000K, 5700K  <b>Rated Life</b> 50,000 hours  <b>Warranty</b> 5 years</p>

Remarks: Input voltage: 100 ~ 240Vac 50/60Hz

